



Material Safety Data Sheet

- 1. Identification:** Product: AC A1430-B
- 2. Product Class:** Mixture of Epoxies
Contain antimony based photoinitiator
Generic Name: Epoxy liquid compound resins

3. Ingredients

Materials	<u>CAS Number</u>
Liquid Epoxy resins (20-40%)	25085-99-8
Solid epoxy resins (30-70%)	25036-25-3
UVI-6992 photoinitiator (Triarylsulfonium hexafluorophosphate salt in propylene carbonate, 1:1 ratio) (0.5% to 2%)	75482-18-7 / 74227-35-3

4. Physical Data

D.O.T.Hazard class: None
Flammability: No
Flash point: > 220 °C
Volatiles by wt. < 0.1%
Water Soluble: Not
Explosion Data:
Sensitivity to Impact: None
Sensitivity to static discharge: None
Other factors: exposure to high heat above 45 degree C or UV light/sun light may cause a nonhazardous polymerization reaction.

5. Hazard Rating:

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 1
PROTECTIVE: B

Hazard Rating: 4 = Extreme, 3 = serious, 2 = Moderate, 1 = Slight, 0 = minimal, B = Gloves and Eye Protection

6. Reactivity Data and Health Hazard Data

The epoxy resins are classified as irritant.
Stability: Stable materials.
Physical Hazards: Unstable (reactive) upon depletion of inhibitor
Swallowing: do not take internally – swallowing may cause nausea, vomiting and diarrhea.
Skin contact: Skin irritation potential.
Inhalation: no evidence of adverse effects from vapors generated at ambient temperatures and atmospheric pressure from available information.
Eye contact: avoid eye contact; wear eye protective glasses with side-shield.
Carcinogenicity: no
Teratogenicity: no
Reproductive toxicity: no



mutagenicity: no

Acute Health Effects: Skin and eye irritant

Chronic Health Effects: No appropriate human or animal chronic health effects data are known to exist.

Route of Exposure

INHALATION: No significant signs or symptoms indicative of adverse health hazard are expected to occur at standard conditions due to the low volatility of the adhesives. Aerosols, or vapors which may be generated at elevated processing temperature may cause respiratory tract irritation. Symptoms of irritation may include coughing, mucous production and shortness of breath.

EYE CONTACT – Primary route

Although no appropriate human or animal health effects data are known to exist, these materials are expected to cause slight eye irritation.

SKIN ABSORPTION

Although no appropriate human or animal health effects data are known to exist, these materials are not expected to be a health hazard by skin absorption.

SKIN IRRITATION – Primary route

Although no appropriate human or animal health effects data are known to exist, these materials are expected to cause slight skin irritation, and may cause an allergic skin reaction (sensitization) in susceptible individuals upon repeated exposure.

INGESTION

No appropriate human or animal health effects data are known to exist.

7. Emergency First Aid Procedures

Swallowing – wash mouth out with water – call physician.

Skin contact: wash skin with water and soap.

Inhalation: get in some fresh air, and call physician if any symptoms appear.

Eyes: Flush eyes with water for at least 15 minutes and call physician.

Emergency medical treatment procedures – remove clothing and rinse skin with water. Look for burns or sign of allergic reaction.

8. Spill and Leak Procedures

Do not discharge to waterways

Clean up using inert solvent and dispose the spilled epoxy-solvent mixture under Federal, State and local regulations. Avoid over loading plant biomass.

9. Fire and Explosion Procedures

These epoxy resins are 100% solid and are not classified as flammable materials (flash point > 220 °C)

Fire fighting procedure for the event of small fires: water will reduce the intensity of the flames.

Fire extinguisher can be used to put out the small fires.

10. Personal Protection

Hands: Protect hands with Nitrile or Latex gloves
Eyes: Eye glasses with side-shield or goggles are required
Ventilation: general room ventilation is expected in normal usage and storage. Special local ventilation may be needed if used at elevated temperatures.

Other hygienic and work practices: use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities.

11. **Storage Requirements:** Store at 15 to 27°C

12. **Special Shipping Information:** UN-Number: Not regulated

13. **Special Label Information:**

Use Statement:

For Industrial Use Only
Keep Out of Reach of Children

Signal Word

Caution

Physical Hazard

Unstable (reactive) Upon Loss of Inhibitor

Health Hazards

May Cause Slight Eye and Skin Irritation
May Cause Allergic Skin Reaction

Precautionary Measures

Do Not Handle Near Heat, Sparks, or Open Flame
Avoid Oxidizing Agents
Use Only with Adequate Ventilation/Personal Protection
Keep Container Closed When Not In Use
Avoid Contact with Eyes, Skin, and Clothing
Avoid Contact with Skin
Do Not Take Internal, Taste or Swallow
Prevent Contact with Food, Chewing, or Smoking Materials
Wash Thoroughly After Handling

Prepared by Addison Clear Wave Coatings, Inc.

Telephone: +1 630-444-1658

Emergency Telephone: +1 630-444-1658

Updated on: May, 2007

The data included herein are presented according to Addison Clear Wave's best practices, and made available solely for the consideration of the original recipients. It is the responsibility of the recipient of this data to remain currently aware on chemical hazard information, and to comply with all national, federal, state and local regulatory requirements applicable to safety, health and environmental protection.